



**DP715/710** is the next generation of powerful, affordable, high quality and simple to use DECT cordless IP phone for small business and residential users. It features compact size, superb voice quality, rich feature set, market leading price-performance and wide range radio coverage which allow users to enjoy the benefits of mobility and voice-over-IP for a minimum investment. DP715/710 is fully compliant with SIP/DECT standard and field proven for flexible deployment.

## Feature Highlights

- DECT base station allows up to 5 registered DECT handsets and up to 4 concurrent calls simultaneously
- When multiple handsets share the same SIP account, Hunting Group supports the following flexible options:
  - Linear Mode: all phones ring sequentially in the predestinated order
  - Shared Line Mode: all phones ring concurrently and always share the same line similar to analog phones
  - Parallel Mode: all phones ring concurrently and after one phone answers, the remaining available phones can place new calls
- Advanced telephony features including caller ID, call waiting, 3-way conference, transfer, forward, do not disturb, message waiting indication, auto answer, multi-language voice prompt, flexible dial plan
- Support comprehensive voice codecs including G.711, G.723.1, G.729A/B, G.726 and iLBC
- Secure communications by using SIP over TLS and SRTP, automated provisioning using HTTP/HTTPS/TFTP/AES-256
- 10-hour talk time, 80-hour standby time, 16-hour charging time

<b>Air Interface</b>	Telephony standards: DECT / GAP (Freq. range: 1880 ~ 1900 MHz (Europe), 1920 ~ 1930 MHz (US)) Number of channels: 120 (Europe) or 60 duplex (US) channels Emission power: 10 mW (average power per channel) Range: up to 300 meters outdoor and 50 meters indoor
<b>Network Interface</b>	One 10/100Mbps auto-sensing Ethernet port (RJ45, Base Station only)
<b>LED Indicators</b>	Base Station: Power, Network, Register, Call
<b>Handset Display</b>	1.7" 102x80 FSTN LCD with blue color backlight
<b>Voice over Packet Capabilities</b>	Base Station: Dynamic Jitter Buffer Handset: Speakerphone with Acoustic Echo Cancellation
<b>Voice Compression</b>	G.711 with Annex I (PLC) and Annex II (VAD/CNG), G.723.1, G.726-32 AAL2, G.729A/B, iLBC
<b>Telephony Features</b>	Caller ID display or block, Call Waiting, Flash, Blind or Attended Transfer, Forward, Hold, Do Not Disturb, 3-Way Conference
<b>QoS</b>	Layer 2 (802.1Q VLAN/802.1p), Layer 3 (ToS, DiffServ, MPLS)
<b>IP Transport</b>	RTP/RTCP
<b>DTMF Method</b>	In-Audio, RFC2833 and/or SIP INFO
<b>IP Signaling</b>	SIP (RFC 3261)
<b>Multiple SIP accounts per base station</b>	Up to five (5) distinct SIP accounts per system; Independent SIP account per handset; Multiple handsets per SIP account
<b>Hunting Group</b>	Linear mode, Parallel mode, Shared Line mode
<b>Provisioning</b>	HTTP, HTTPS, TFTP, TR-069 (pending), secure and automated provisioning
<b>Security</b>	TLS, SRTP, HTTPS
<b>Management</b>	Web interface or via secure (AES encrypted) central configuration file for mass deployment; support device configuration via built-in IVR, Web browser or central configuration file through TFTP, HTTP or HTTPS
<b>Phonebook (per handset)</b>	200 records each with up to 24 digits and up to 16 characters; 10 dialed call records, 30 received call records
<b>Multi-language Display (Handset LCD Menu)</b>	English, French, German, Spanish, Dutch, Italian, Czech, Danish, Greek, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
<b>Polyphonic Ringtones</b>	18 different ringer melodies are available to indicate an incoming call (internal intercom or external VoIP)
<b>Universal Power Supply</b>	Input: 100-240VAC, 50-60Hz, 0.15A; Output: 6VDC, 500mA (for Base Station); 7VDC, 420mA (for Charger Unit)
<b>Battery Life</b>	10-hour talk time, 80-hour standby time, 16-hour charging time
<b>Dimensions (H x W x D)</b>	Base Station: 75 x 105 x 85mm; Handset: 160 x 46 x 22mm; Charger Unit: 53 x 75 x 60mm
<b>Weight</b>	Base Station: 95g; Handset (with batteries): 104g; Charger Unit: 102g
<b>Environmental</b>	Operational: 32° ~ 104°F or 0° ~ 40°C; Storage: - 4° ~ 140°F or -20° ~ 60°C Humidity: Maximum 85% Non-condensing
<b>Compliance</b>	FCC Part 15B/15D; CE: ETSI EN 301 489-1 V1.8.1, ETSI EN 301 489-6 V1.3.1, ETSI EN 301 406-1 V2.1.1, ETSI EN 301 406 V1.5.1, EN60950-1; RoHS; UL(Power Supply)

**DP715:**  
Handset + Base Station



**DP710:**  
Handset + Charger Unit

