





ALCATEL
home & business phones

Temporis IP150



A high-performing SIP phone

- Full duplex handsfree to ease your conference calls
- Headset support for your convenience in office environments
- 10 speed dial memories for one-touch access to your top contacts
- Dual-color BLF to easily monitor your lines
- Access to local and network phonebooks for enhanced contact management
- Comfortable backlit display giving access to many business features

-  Backlit graphical display
-  Full duplex handsfree
-  10 function keys
-  2 SIP accounts

Temporis IP150



Commercial reference

3700601409444

Main features

- 158x57 backlit graphical display
- 2 sip accounts
- Power over Ethernet
- Full duplex handsfree
- RJ9 headset port and headset key
- Call log: 100 entries (received, dialed, missed)
- Phonebook: local (100 entries, downloadable), LDAP
- Built-in languages : 7

Function support

- Multiple call operation (up to 6)
- 10 function keys, 5 of them dual-color backlit (up to 18 virtual keys)
- 10 speed dial memories (press and hold)
- Alert indicators (incoming call, MWI, no service, headset, mute)
- Mute, hold, transfer , call forward, redial, 3-way conference
- 10 built-in melodies
- Do Not Disturb
- Auto answer , call return
- Volume control (handset, speakerphone, headset and ringers)
- Dial plans
- Anonymous call, ACR
- System or custom logo*

IP PBX integration

- Network conference
- BLF, BLA
- DND&CF sync
- Intercom, paging, music on hold
- Group pickup, call park

Key pad

- 3 softkeys
- Menu, Hold, Cancel
- 10 line/function programmable keys (18 virtual keys)
- 5 way navigation key
- Redial, access to voicemail, call history
- Volume up and down, mute , hands free and headset keys

Interfaces

- 2 RJ-45 auto sensing 10/100Mps (one for LAN and one for PC)
- 1 RJ-9 port for handset connection
- 1RJ-9 port for headset connection
- 5Vdc power jack

Technical Specifications

VoIP Protocol Support :

- SIPv2 (RFC3261)

Voice Features :

- G722, G711A, G711u, G726, G729ab
- VAD, CNG, AEC, PLC, AJB, AGC
- Full duplex speakerphone

Network Features:

- DHCP/Static
- DNS Srv, Redundant server support
- STUN
- DTMF: In band, RFC2833, SIP Info
- 802.1x, LLDP
- QOS 802.1p/Q, DSCP

Security Features:

- TLS
- SRTP
- HTTPS with mutual certificate authentication
- Config file AES encryption
- 2 level access privileges (user/admin)

Configuration and Management

IP address Assignment :

- DHCP, Static IP

Configuration Support :

- Keypad
- Web browser management (Admin/User), HTTP/HTTPS)
- Autoprovision with HTTP/HTTPS/TFTP, APRT support
- Pcap tracing, syslog

Physical & Environmental

Mounting :

- Multiposition adjustable footstand: 2
- Wall mountable

Power over Ethernet :

- 802.3af, class 2

Power Adaptor :

- AC100-240V input, 5Vdc/700mA output (not included, order separately)

Power consumption:

- 0.9-2.1W

Operating temperature :

- From -5 to 45°C

Operating Humidity :

- Up to 95% non-condensing

Storage temperature :

- Up to 60°C

*Soon available

Sales & Marketing Department: ATLINKS Europe-22 Quai Gallieni-92150 Suresnes-France. ATLINKS Europe is a simplified joint stock company capitalized at €500,000. Registered under no. 508 823 747 in the Nanterre Trade and Business Register. The manufacturer reserves the right to change product features to deliver technical improvements or comply with new regulations. The Alcatel logo and Alcatel name are trademarks of Alcatel-Lucent and are used under license by ATLINKS Europe. © Copyright ATLINKS 2014. Reproduction prohibited. Photos are non-contractual