



# Enterprise-Level Communications Server For Growing Businesses

The ISS UCR Business 450 is a standard 19" 2U appliance. It allows users to integrate up to 2 pieces of PCIe telephony interface cards, with any combinations of analog, BRI, PRI, GSM or transcoding interfaces.

RAID 1 optional support provides better data backup, reliability and read performance.

Optional HDD case provides hot swapping function for the storage device. ISS UCR Business 450 includes an LCD, convenient for you to check the IP address, System Load and so on. Additionally, ISS UCR Business 450 series provides an optional redundant power supply for high availability.

Capable of comprehensive protocol processing including SIP, H.323 protocols in IP side, BRI, PRI, SS7, GSM and some transcoding protocols in CPE.

Taking the full advantages of powerful open source platforms, the ISS UCR Business 450 is preloaded with Issabel® IPPBX software.



4  
↓ E1

120  
☎

300  
☎

• Basic • PRO

☎ – Concurrent Calls    ☎ – Extensions

# ISS UCR Business 450 Basic|PRO™

Learn more at:

[www.issabel.com](http://www.issabel.com)

## ⚙️ Technical Specifications

### HARDWARE

- **CPU: 4 Core Intel Celeron N2930 1.83GHz**
- **RAM: 4 GB DDR3L (Default) Up to 8GB DDR3L**
- **1st Hard Drive : 500 GB HDD**
- **2nd Hard Drive: 500 GB HDD (PRO)**
- **RAID Support (PRO)**
- **SSDs Support (Optional)**
- **2 PCIe slots**
- **Network Interfaces: Up to 2 Ethernet Channels (10/100/1000Mbps Speed)**
- **VGA: 1**

- **USB Ports: 2**
- **Power switch**
- **Redundant power supply (PRO)**
- **LCD**
- **Fan**
- **Rack mountable**
- **Warranty: 1 year**

### OPERATION SPECIFICATIONS

- **Operation Voltage: 100-240V AC , 50/60Hz**

### PHYSICAL SPECIFICATIONS

- **Height 8.8 cm**
- **Width 44 cm**
- **Depth 37.5 cm**
- **Weight 5200g**

*"Business 450 is an open source Issabel-based complete IPPBX solution for SMB's. With affordable price, users may easily setup their customized Communications"*

### Issabel LLC.

ISSABEL EMEA  
+(34) 94 477 22 35

ISSABEL LATAM  
+52 (55) 1164 7616