


V64 Prime Business Phone

V64 is more than an efficient telephone but a delicate work of art, providing a smart and smooth business communication experience for enterprises. As the prime business phone featuring a color LCD screen and built-in Bluetooth 4.2 and 2.4G/5G Wi-Fi, V64 is a perfect combination of elegant outside and powerful inside.

Highlights

- ✓ 3.5" color LCD screen
- ✓ Support audio codec G.722 and Opus, HD audio on speakerphone and handset
- ✓ Support 6-party local conference
- ✓ Available to link with security products, can be easily customized into various security solutions for reducing investment
- ✓ Built-in 2.4GHz/5G WiFi and Bluetooth 4.2, realizing more flexible connectivity
- ✓ Dual Gigabit ports, integrated PoE
- ✓ Two installation methods of desktop stand and wall mountable
- ✓ Up to 21 DSS keys, every DSS key can be set as Line/BLF/ Speed Dial Key



Generic

- 12 SIP lines
- HD voice
- PoE enabled
- 3.5-inch (480x320) color screen
- Handset / hands-free / headset mode
- Intelligent DSS keys
- Desktop Stand / Wall-mounted (need an additional wall hanging parts)
- Optional external power supply

Phone Features

- Local Phonebook (1000 entries)
- Remote Phonebook (XML/LDAP, 1000 entries)
- Call logs (In/out/missed, 1000 entries)
- Blocked list/Allowed list
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Built-in Bluetooth 4.2: Support Bluetooth headset/ Pairing mobile devices
- Built-in Wi-Fi
 - ✓ 2.4GHz, 802.11 b/g/n
 - ✓ 5GHz, 802.11 a/n/ac
- Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)

- Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- Support Recording(through server)
- Action URL / Active URI
- uaCSTA
- SIP Hotspot
- Multicast
- Action Plan
- Group listening

Call Features

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- BLF
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (With server)

- 6-way Conference
- Hot Line
- Hotdesking

Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- HAC handset
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.723.1, G.726, G.729, G.729A, G.729B, G.729AB, iLBC
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR) / Automatic Gain Control (AGC)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)
- VQM voice quality monitoring

Network

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static IP / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: OpenVPN/L2TP
- VLAN
- LLDP
- CDP
- QoS
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- WIFI: WI-FI Security Mode: WPA /WPA2-PSK/802.X EAP

Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- CDP
- LLDP
- PPPoE
- 802.1x
- OpenVPN
- SNTP
- FTP/TFTP

- HTTP/HTTPS

- TR-069
- AES128 & AES256

Deployment & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

Physical Specifications

- LCD: 3.5 inch (480x320) color screen
- Keypad: 39 keys, including
 - 8 DSS keys with LED indicator light
 - 6 Function keys (Contact, Hold, MWI, Mute, Headset, Redial)
 - 4 Soft-keys
 - 4 Navigation keys
 - 1 OK key
 - 1 Return key
 - 12 Standard Phone Digits keys
 - 2 Volume Control keys, Up/Down
 - 1 Hands-free key
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5.E Ethernet Cable x1
- Desk Stand x1
- Status Indicator Light x1 (Red)
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- USB2.0 Port x1: Standard A, Connect with Flash Driver&USB headset
- Security lock port x1
- Power: DC5V/2A or PoE
- Power dissipation: standby 0.92W, high: 5.85W (Power supply)
- Power dissipation: standby 1.59W, high: 7.29W (POE)
- Working Temperature: 0~45℃
- Working Humidity: 10~95%
- Installation:
 - Desktop Stand
 - Wall-mounted (need an additional wall hanging parts)
- Color: Gunmetal
- Qty/CTN: 10 pcs
- N.W/CTN: 11.8 kg
- G.W/CTN 12.924 kg
- Device Dimensions: 204x202x31mm
- Gift Box Dimensions: 307x258x71 mm
- Outer CTN Dimensions: 5536x380x327 mm (10 PCS)

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products. For more information, please visit: www.fanvil.com

