

## Cisco SRW2024 24-Port Gigabit Switch: WebView Cisco Small Business Managed Switches

Highly Secure, Reliable, Intelligent Switching for Your Growing Businesses

### Highlights

- 24 high-speed ports optimized for the network core or to support bandwidth-intensive applications
- Enhanced QoS helps ensure a consistent network experience and supports networked applications including voice, video, and data storage
- Strong security protects network traffic to keep unauthorized users off the network
- Simplified, web-based management for easy installation and configuration

**Figure 1.** Cisco SRW2024 24-Port Gigabit Switch: WebView



### Product Overview

Growing businesses require cost-effective networking solutions that can scale with ever-changing business needs. The Cisco® SRW2024 24-Port Gigabit Switch (Figure 1) brings Gigabit speeds to your users and servers while increasing the intelligence and security of the network infrastructure. The twenty-four 10/100/1000 Mbps ports enable you to take advantage of the Gigabit Ethernet interfaces shipping in the current generation of servers, workstations, and storage devices, in addition to supporting your existing 10/100 Mbps clients. The optional Gigabit optical interfaces allow you to expand the network as your business grows.

Network security is a top priority in any size business. Most business data networks, large and small, are insecure. Unauthorized access to the network and mission-critical data is a constant concern. The Cisco SRW2024 helps secure the network through 802.1X port authentication and MAC filtering. The 802.1X standard requires clients to authenticate themselves before the port will pass data for them.

Businesses are recognizing the benefits of voice over IP (VoIP) and are quickly migrating their voice services to IP-based platforms, requiring their local area networks to support both voice and data applications. In unmanaged IP networks, bursty data sessions can disrupt voice packet delivery, causing poor voice quality. With the enhanced quality of service (QoS) and traffic-

management features in the Cisco SRW2024, voice data can be prioritized, helping ensure clear and reliable voice communications.

Taking advantage of the advanced features of the Cisco SRW2024 can further secure the integrity of your network. The WebView interface provides an intuitive, highly secure management interface, enabling you to better utilize the comprehensive feature set of the switch, for a better-optimized, more secure network.

## Features

- Twenty-four 10/100/1000 switched RJ-45 ports with auto medium dependent interface (MDI) and MDI crossover (MDI-X) cable detection
- 2 mini Gigabit Interface Converter (mini-GBIC) slots for fiber and copper Gigabit Ethernet expansion (shared)
- Nonblocking, store-and-forward switching mechanism
- Simplified QoS management enabled by advanced queuing techniques using 802.1p, differentiated services (DiffServ), or type of service (ToS) prioritization schemes enhances the performance of real-time applications such as voice and video
- Configuration and monitoring from a standard web browser with WebView management
- Secure remote management of the switch via Secure Shell (SSH) and SSL secure channel network protocols
- 802.1Q-based VLANs enable segmentation of networks for improved performance and security
- Private VLAN Edge (PVE) for simplified network isolation of guest connections or autonomous networks
- Automatic configuration of VLANs across multiple switches through Generic VLAN Registration Protocol (GVRP) and Generic Attribute Registration Protocol (GARP)
- Automatic port configuration through auto MDI/MDIX and 802.1ab with Link Layer Discovery Protocol (LLDP) and Universal Plug and Play (UPnP) support
- User/network port-level security via 802.1X authentication and MAC-based filtering
- Increased bandwidth (up to 8x) and added link redundancy with Link Aggregation Control Protocol (LACP)
- Enhanced rate-limiting capabilities provide control, including back pressure to control the rate at which data can flow into and out of a port
- Multicasting, broadcasting, and flooding control
- Port mirroring for noninvasive monitoring of switch traffic
- Jumbo frame support (10 KB)
- Simple Network Management Protocol (SNMP) versions 1, 2c, and 3 and Remote Monitoring (RMON) support
- Fully rack mountable using the included rack-mounting hardware

## Specifications

Table 1 contains the specifications, package contents, and minimum requirements for the Cisco SRW2024 24-Port Gigabit Switch.

**Table 1.** Specifications for the Cisco SRW2024 24-Port Gigabit Switch: WebView

Specifications	
<b>Standards</b>	IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.1p, 802.1Q
<b>Ports</b>	Twenty-four 10/100/1000 RJ-45 ports and 2 shared Mini-GBIC slots
<b>Cabling type</b>	Category 5 Ethernet or better
<b>LEDs</b>	System, Link/Activity, Gigabit
Performance	
<b>Switching capacity</b>	48 Gbps, nonblocking
<b>MAC table size</b>	8000
<b>Number of VLANs</b>	256 - static
Management	
<b>Web user interface</b>	Built-in web user interface for easy browser-based configuration (HTTP/HTTPS)
<b>SNMP</b>	SNMP versions 1, 2, and 3 with support for traps
<b>SNMP MIBs</b>	RFC1213 MIB-2, RFC2863 interface MIB, RFC2665 Ether-like MIB, RFC1493 bridge MIB, RFC2674 extended bridge MIB (P-bridge, Q-bridge), RFC2819 RMON MIB (groups 1,2,3,9 only), RFC2737 entity MIB, RFC 2618 RADIUS client MIB
<b>RMON</b>	Embedded RMON software agent supports 4 RMON groups (history, statistics, alarms, and events) for enhanced traffic management, monitoring, and analysis.
<b>Firmware upgrade</b>	<ul style="list-style-type: none"> <li>• Web browser upgrade (HTTP)</li> <li>• Trivial File Transfer Protocol (TFTP) upgrade</li> </ul>
<b>Port mirroring</b>	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe
<b>Other management</b>	<ul style="list-style-type: none"> <li>• RFC854 Telnet (menu-driven configuration)</li> <li>• SSH and Telnet management</li> <li>• Telnet client</li> <li>• SSL security for web user interface</li> <li>• Switch audit log</li> <li>• Dynamic Host Configuration Protocol (DHCP) client</li> <li>• BOOTP</li> <li>• Simple Network Time Protocol (SNTP)</li> <li>• Xmodem upgrade</li> <li>• Cable diagnostics</li> <li>• Ping</li> <li>• Traceroute</li> </ul>
Security Features	
<b>IEEE 802.1X</b>	802.1X - RADIUS authentication; MD5 encryption
<b>Access control lists (ACLs)</b>	<ul style="list-style-type: none"> <li>• Differentiated services code point (DSCP)/IP precedence-based class of service (CoS)</li> <li>• IPv6 traffic-class-based CoS</li> <li>• IP address</li> <li>• Subnet mask</li> <li>• Protocol</li> <li>• Service type</li> <li>• MAC address</li> <li>• VLAN ID</li> <li>• TCP/ User Datagram Protocol (UDP) port</li> </ul>
Availability	
<b>Link aggregation</b>	<ul style="list-style-type: none"> <li>• Link aggregation using IEEE 802.3ad LACP</li> <li>• Up to 8 ports in up to 8 trunks</li> </ul>

<b>Storm control</b>	Broadcast, multicast, and unknown unicast
<b>Spanning Tree</b>	IEEE 802.1d Spanning Tree, IEEE 802.1s Multiple Spanning Tree, IEEE 802.1w Rapid Spanning Tree, Fast Linkover
<b>IGMP snooping</b>	IGMP (versions 1 and 2) snooping provides for fast client joins and leaves of multicast streams and limits bandwidth-intensive video traffic to only the requestors.
<b>QoS</b>	
<b>Priority levels</b>	4 hardware queues
<b>Scheduling</b>	Priority queuing and weighted round-robin (WRR)
<b>Class of service</b>	<ul style="list-style-type: none"> <li>• Port based</li> <li>• 802.1p VLAN priority based</li> <li>• IP ToS/differentiated services code point (DSCP) based</li> <li>• IPv4 and IPv6 traffic class based</li> </ul>
<b>Rate limiting</b>	Ingress policer, egress shaper
<b>Layer 2</b>	
<b>VLAN</b>	<ul style="list-style-type: none"> <li>• Port-based and 802.1Q-based VLANs</li> <li>• PVE</li> <li>• Management VLAN</li> </ul>
<b>Head-of-line (HOL) blocking</b>	HOL blocking prevention
<b>Jumbo frame</b>	Supports frames up to 10 KB
<b>Dynamic VLAN</b>	GVRP - dynamic VLAN registration
<b>Standards</b>	802.3i 10BASE-T Ethernet, 802.3u 100BASE-TX Fast Ethernet, 802.3ab 1000BASE-T Gigabit Ethernet, 802.3z Gigabit Ethernet, 802.3x flow control
<b>Environmental</b>	
<b>Dimensions W x H x D</b>	16.93 x 1.75 x 13.78 (430mm x 44.5mm x 350mm)
<b>Unit weight</b>	7.54 lbs (3.42kg)
<b>Power</b>	100-240V, 50-60Hz, internal, universal
<b>Certification</b>	FCC Part 15 Class A, CE Class A, UL, cUL, CE mark, CB
<b>Operating temperature</b>	0° to 40°C (32° to 104°F)
<b>Storage temperature</b>	-20° to 70°C (-4° to 158°F)
<b>Operating humidity</b>	10% to 90%
<b>Storage humidity</b>	10% to 95%
<b>Package Contents</b>	
<ul style="list-style-type: none"> <li>• Cisco SRW2024 24-Port Gigabit Switch</li> <li>• AC power cord</li> <li>• Rack-mounting kit with brackets and hardware</li> <li>• CD with user guide in PDF format</li> <li>• Registration card</li> <li>• Console cable</li> </ul>	
<b>Minimum Requirements</b>	
<ul style="list-style-type: none"> <li>• Category 5 Ethernet network cable</li> <li>• TCP/IP installed on each computer within the network</li> <li>• Network adapter installed in each computer</li> <li>• Network operating system (Windows, Linux, Mac OS X)</li> </ul>	
<b>Product Warranty</b>	
5-year limited hardware warranty with return to factory replacement and 90-day limited software warranty	

## Cisco Limited Warranty for Cisco Small Business Series Products

This Cisco Small Business product comes with a 5-year limited hardware warranty with return to factory replacement and a 90-day limited software warranty. In addition, Cisco offers software application updates for bug fixes and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to:

<http://www.cisco.com/go/smallbiz>.

Product warranty terms and other information applicable to Cisco products are available at

<http://www.cisco.com/go/warranty>.

### For More Information

For more information on Cisco Small Business products and solutions, visit:

<http://www.cisco.com/smallbusiness>.



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

CCDE, CCENT, CCSI, Cisco Eos, Cisco Explorer, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco TrustSec, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), CiscoFinanced (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLYNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1002R)

Printed in USA

C78-502265-02 03/10